

TSQ2Q-85L-XXXC Active Optical Cable

Multi-Mode 200G BASE SR4 QSFP56 TO 2x100G BASE SR2 QSFP56 Active Optical Cable, With Diagnostic Monitoring

Features

- SFF-8665 compliant QSFP56 form factor
- Data rate up to 53.125 Gbps per lane
- Maximum link length of 70m on OM3 MMF and 100m on OM4 MMF
- 4 channels 850nm VCSEL array (200G End)
- 4 channels PIN photo detector array (200G End)
- Single 3.3V power supply
- Low power dissipation < 5.5W (Each End)
- Built-in digital diagnostic functions
- Operating case temperature: 0°C~+70°C
- RoHS6 compliant (lead free)

Applications

- 200GBASE-SR4 Ethernet

Product Description

The TSQ2Q-85L-XXXC is a 4-Channel, Pluggable, Parallel, Fiber-Optic 200G QSFP56 to 2X100G QSFP56 AOC. This transceiver is a high performance module for short-range multi-lane data communication and interconnect applications. It integrates 4 data lanes in each direction with 200Gbps bandwidth.

These modules are designed to operate over multimode fiber systems using a nominal wavelength of 850nm. The electrical interface uses a 38@QSFP56 contact edge type connector

Absolute Maximum Rating

These values represent the damage threshold of the module. Stress in excess of any of the individual Absolute Maximum Ratings can cause immediate catastrophic damage to the module even if all other parameters are within Recommended Operating Conditions.

Parameters	Symbol	Min.	Max.	Unit
Power Supply Voltage	VCC	-0.5	+3.6	V
Storage Temperature	Tc	-40	+85	°C
Relative Humidity ¹	RH	15	85	%

Notes:

1. Non-condensing.

Recommended Operating Environment

Recommended Operating Environment specifies parameters for which the electrical and optical characteristics hold unless otherwise noted.

Parameter	Symbol	Min	Typical	Max	Unit
Power Supply Voltage	VCC	3.15	3.30	3.45	V
Case Operating Temperature	Tca	0	-	70	°C
Fiber Bend Radius	Rb	3	-	-	cm


Electrical characteristics

Parameter	Symbol	Min	Typical	Max	Unit
Signaling rate per lane	-	53.125			Gbps
Differential Input Voltage Amplitude	Vin	300	-	900	mV
Differential termination mismatch	-	-	-	10	%
Input Logic Level High	VIH	2.0	-	VCC	V
Input Logic Level Low	VIL	0	-	0.8	V
Output Logic Level High	VOH	VCC-0.5	-	VCC	V
Output Logic Level Low	VOL	0	-	0.4	V

Notes:

1. Differential input voltage amplitude is measured between TxnP and TxnN.

QSFP56 Transceiver Electrical Pad Layout




Pin Definition

Pin	Symbol	Name/Description
1	GND	Ground
2	Tx2n	Transmitter Inverted Data Input
3	Tx2p	Transmitter Non-Inverted Data Input
4	GND	Ground
5	Tx4n	Transmitter Inverted Data Input
6	Tx4p	Transmitter Non-Inverted Data Input
7	GND	Ground
8	ModSelL	Module Select
9	ResetL	Module Reset
10	Vcc Rx	+3.3 V Power supply receiver
11	SCL	2-wire serial interface clock
12	SDA	2-wire serial interface data
13	GND	Ground
14	Rx3p	Receiver Non-Inverted Data Output
15	Rx3n	Receiver Inverted Data Output
16	GND	Ground
17	Rx1p	Receiver Non-Inverted Data Output
18	Rx1n	Receiver Inverted Data Output
19	GND	Ground

20	GND	Ground
21	Rx2n	Receiver Inverted Data Output
22	Rx2p	Receiver Non-Inverted Data Output
23	GND	Ground
24	Rx4n	Receiver Inverted Data Output
25	Rx4p	Receiver Non-Inverted Data Output
26	GND	Ground
27	ModPrsL	Module Present
28	IntL	Interrupt
29	VCC Tx	+3.3 V Power supply transmitter
30	VCC1	+3.3 V Power Supply
31	LPMode	Low Power Mode
32	GND	Ground
33	Tx3p	Transmitter Non-Inverted Data Input
34	Tx3n	Transmitter Inverted Data Input
35	GND	Ground
36	Tx1p	Transmitter Non-Inverted Data Input
37	Tx1n	Transmitter Inverted Data Input
38	GND	Ground

Mechanical



Length tolerance table:

L	Tolerance (mm)
$L \leq 1 \text{ M}$	$+70/-0$
$1 \text{ M} < L < 7 \text{ M}$	$+100/-0$
$L \geq 7 \text{ M}$	$+2\%L/-0$

Ordering Information

Part Number	Product Description
TSQ2Q-85L-XXXC	200G BASE SR4 QSFP56 TO 2x100G BASE SR2 QSFP56 AOC 0°C ~ +70°C
XXX :001~070,1~70 Length in meters on OM3 MMF	
XXX :001~100,1~100 Length in meters on OM4 MMF	

References

1. QSFP MSA Specification.
2. IEEE 802.3cd 200GBASE-SR4 specification.

Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by T&S before they become applicable to any particular order or contract. In accordance with the T&S policy of continuous improvement specifications may change without notice.

The publication of information in this data sheet does not imply freedom from patent or other protective rights of T&S or others. Further details are available from any T&S sales representative.