


TSDR4-NCNMC3C Optical Transceiver

1310nm QSFP-DD 400G BASE DR4 Transceiver, With Diagnostic Monitoring
Duplex QSFP-DD 500m Transceiver

Features

- Hot-pluggable QSFP-DD form factor
- Parallel 4 Optical Lanes
- MPO-12 connector
- Compliant to QSFP-DD MSA
- IEEE 802.3bs 400GBASE-DR4 Specification compliant
- Data Rate 106.25Gbps PAM4 per lane
- 8x53.125Gb/s electrical interface (400GAUI-8)
- Up to 500m transmission on single mode fiber (SMF) with FEC
- Digital diagnostics functions are available via the I2C interface
- Single 3.3V Power Supply and Power Dissipation < 10W
- Operating Case Temperature: 0°C~+70°C
- RoHS compliant 

Applications

- 400G Ethernet
- Infiniband Interconnect
- Data center
- Enterprise Networking

Production Description

This product is a 400Gb/s Quad Small Form Factor Pluggable-double density (QSFP-DD) optical module designed for 500m optical communication applications. The module converts 8 channels of 50Gb/s (PAM4) electrical input data to 4 channels of parallel optical signals, each capable of 100Gb/s operation for an aggregate data rate of 400Gb/s. Reversely, on the receiver side, the module converts 4 channels of parallel optical signals of 100Gb/s each channel for an aggregate data rate of 400Gb/s into 8 channels of 50Gb/s (PAM4) electrical output data.

An optical fiber cable with an MTP/MPO-12 connector can be plugged into the QSFP-DD DR4 module receptacle. Proper alignment is ensured by the guide pins inside the receptacle. The cable usually cannot be twisted for proper channel to channel alignment. Electrical connection is achieved through an QSFP-DD MSA-compliant edge type connector.

The product is designed with form factor, optical/electrical connection and digital diagnostic interface

according to the QSFP-DD Multi- Source Agreement (MSA) Type 2. It has been designed to meet the harshest external operating conditions including temperature, humidity and EMI interference.

Absolute Maximum Rating

These values represent the damage threshold of the module. Stress in excess of any of the individual Absolute Maximum Ratings can cause immediate catastrophic damage to the module even if all other parameters are within Recommended Operating Conditions.

Parameters	Symbol	Min.	Max.	Unit
Power Supply Voltage	VCC	-0.5	+3.6	V
Storage Temperature	Tc	-40	+85	°C
Relative Humidity	RH	0	85	%

Recommended Operating Environment

Recommended Operating Environment specifies parameters for which the electrical and optical characteristics hold unless otherwise noted.

Parameter	Symbol	Min.	Typical	Max	Unit
Power Supply Voltage	VCC	3.15	3.30	3.45	V
Operating Case Temperature	Tca	0		70	°C

Electrical Characteristics

The following electrical characteristics are defined over the Recommended Operating Environment unless otherwise specified.

Parameter	Symbol	Min.	Typical	Max	Unit	Notes
Data Rate per lane	DR	-	53.125	-	Gbps	
Transmitter						
Input differential impedance	Rin	90	100	110	Ω	
Differential Input Voltage swing	Vin	900	-	1100	mVp-p	
Receiver						
Differential Output Swing	Vout	-	-	900	mVp-p	
Output differential impedance	Rout	90	100	110	Ω	

Optical Characteristics

The following optical characteristics are defined over the Recommended Operating Environment unless otherwise specified.

Parameter	Symbol	Min.	Typical	Max	Unit	Notes
Transmitter						
Center Wavelength	λ	1304.5	1310	1317.5	nm	
Data rate, each lane		53.125 \pm 100ppm			GBd	
Side-mode Suppression Ratio	SMSR	30			dB	
Average Optical Power, per lane	Po	-2.9	-	4	dBm	1
Extinction Ratio	ER	3.5	-	-	dBm	
Optical Modulation Amplitude	OMA	-4.5	-	3	dB	
Transmitter and Dispersion Eye Closure	TDECQ			3.4	dB	
Optical Return Loss Tolerance	ORL	-	-	21.4	dB	
Receiver						
Center Wavelength	λ	1304.5	1310	1317.5	nm	
Data rate, each lane		53.125 \pm 100ppm			GBd	
Average Receive power ,each lane		-5.9		4.0	dBm	
Receive power (OMAouter), each lane				4.2	dBm	
Receiver sensitivity (OMAouter), each lane				-4.4	dBm	
LOS Asserted	Lsa	-15	-	-	dBm	
LOS De-Asserted	Lda	-	-	-8.9	dBm	
LOS Hysteresis	Lh	0.5	-	-	dB	

Note:

[1] Average launch power, each lane (min) is informative and not the principal indicator of signal strength.

[2] A transmitter with launch power below this value cannot be compliant; however, a value above this does not ensure compliance.

Qsfp-Dd Transceiver Electrical Pad Layout




Figure 1 – QSFP-DD -compliant 76-pin connector (per QSFP-DD MSA)

Pin Definition

Pad	Logic	Symbol	Description
1		GND	Ground
2	CML-I	Tx2n	Transmitter Inverted Data Input
3	CML-I	Tx2p	Transmitter Non-Inverted Data Input
4		GND	Ground
5	CML-I	Tx4n	Transmitter Inverted Data Input
6	CML-I	Tx4p	Transmitter Non-Inverted Data Input
7		GND	Ground
8	LVTTL-I	ModSelL	Module Select
9	LVTTL-I	ResetL	Module Reset
10		VccRx	+3.3V Power Supply Receiver
11	LVC MOS-I/O	SCL	2-wire serial interface clock
12	LVC MOS-I/O	SDA	2-wire serial interface data
13		GND	Ground
14	CML-O	Rx3p	Receiver Non-Inverted Data Output
15	CML-O	Rx3n	Receiver Inverted Data Output
16		GND	Ground
17	CML-O	Rx1p	Receiver Non-Inverted Data Output
18	CML-O	Rx1n	Receiver Inverted Data Output
19		GND	Ground
20		GND	Ground
21	CML-O	Rx2n	Receiver Inverted Data Output
22	CML-O	Rx2p	Receiver Non-Inverted Data Output
23		GND	Ground
24	CML-O	Rx4n	Receiver Inverted Data Output
25	CML-O	Rx4p	Receiver Non-Inverted Data Output
26		GND	Ground
27	LVTTL-O	ModPrsL	Module Present
28	LVTTL-O	IntL	Interrupt
29		VccTx	+3.3V Power supply transmitter
30		Vcc1	+3.3V Power supply
31	LVTTL-I	InitMode	Initialization mode; In legacy QSFP applications, the InitMode pad is called LPMODE
32		GND	Ground
33	CML-I	Tx3p	Transmitter Non-Inverted Data Input
34	CML-I	Tx3n	Transmitter Inverted Data Input
35		GND	Ground
36	CML-I	Tx1p	Transmitter Non-Inverted Data Input
37	CML-I	Tx1n	Transmitter Inverted Data Input
38		GND	Ground

Pad	Logic	Symbol	Description
39		GND	Ground
40	CML-I	Tx6n	Transmitter Inverted Data Input
41	CML-I	Tx6p	Transmitter Non-Inverted Data Input
42		GND	Ground
43	CML-I	Tx8n	Transmitter Inverted Data Input
44	CML-I	Tx8p	Transmitter Non-Inverted Data Input
45		GND	Ground
46		Reserved	For future use
47		VS1	Module Vendor Specific 1
48		VccRx1	3.3V Power Supply
49		VS2	Module Vendor Specific 2
50		VS3	Module Vendor Specific 3
51		GND	Ground
52	CML-O	Rx7p	Receiver Non-Inverted Data Output
53	CML-O	Rx7n	Receiver Inverted Data Output
54		GND	Ground
55	CML-O	Rx5p	Receiver Non-Inverted Data Output
56	CML-O	Rx5n	Receiver Inverted Data Output
57		GND	Ground
58		GND	Ground
59	CML-O	Rx6n	Receiver Inverted Data Output
60	CML-O	Rx6p	Receiver Non-Inverted Data Output
61		GND	Ground
62	CML-O	Rx8n	Receiver Inverted Data Output
63	CML-O	Rx8p	Receiver Non-Inverted Data Output
64		GND	Ground
65		NC	No Connect
66		Reserved	For future use
67		VccTx1	3.3V Power Supply
68		Vcc2	3.3V Power Supply
69		Reserved	For Future Use
70		GND	Ground
71	CML-I	Tx7p	Transmitter Non-Inverted Data Input
72	CML-I	Tx7n	Transmitter Inverted Data Input
73		GND	Ground
74	CML-I	Tx5p	Transmitter Non-Inverted Data Input
75	CML-I	Tx5n	Transmitter Inverted Data Input
76		GND	Ground

Ordering Information

Part Number	Product Description
TSDR4-NCNMC3C	400Gbps QSFP-DD DR4 Transceiver, Up to 500m transmission on single mode fiber (SMF) with FEC, 0°C ~ +70°C

Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by T&S before they become applicable to any particular order or contract. In accordance with the T&S policy of continuous improvement specifications may change without notice. The publication of information in this data sheet does not imply freedom from patent or other protective rights of T&S or others. Further details are available from any T&S sales representative.