


10G SFP+ Active Optical Cable TSPA-85192-xxxC

Features

- Electrical interface compliant to SFF-8431
- 850nm VCSEL laser and PIN photo-detector
- Maximum link length of 82m on OM2 MMF and 300m on OM3 MMF
- Hot Pluggable
- Built-in digital diagnostic functions
- Operating case temperature 0°C to 70°C
- RoHS compliant (lead free) 



Applications

- 10G Ethernet

Product Description

T&S SFP+ 10G Active Optical Cables are direct-attach fiber assemblies with SFP+ connectors. They are suitable for very short distances and offer a cost-effective way to connect within racks and across adjacent racks. The module is a Single-Channel, Pluggable, Fiber-Optic SFP+ for 10 Gigabit Ethernet and Infiniband EDR Applications.

This module is designed to operate over multimode fiber systems using a nominal wavelength of 850nm. The electrical interface uses a 20 contact edge type connector.

Absolute Maximum Rating

These values represent the damage threshold of the module. Stress in excess of any of the individual Absolute Maximum Ratings can cause immediate catastrophic damage to the module even if all other parameters are within Recommended Operating Conditions.

Parameters	Symbol	Min.	Max.	Unit
Power Supply Voltage	VCC	-0.5	+3.6	V
Storage Temperature	Tc	-40	+85	°C
Relative Humidity	RH	0	85	%

Recommended Operating Conditions

Parameter	Symbol	Min	Typical	Max	Unit
Supply Voltage	VCC	3.15	3.3	3.45	V
Supply current per end	Icc	-	-	150	mA
Operating Case Temperature	Tca	0	-	70	°C
Data Rate	DR	-	10.3125	-	Gbps
Fiber Bend Radius	Rb	3	-	-	cm

Notes:

- [1] Supply current is shared between VCCTX and VCCRX.
 [2] In-rush is defined as current level above steady state current requirements.


Transmitter Specifications

Parameter	Symbol	Min	Typical	Max	Unit
Input differential impedance	Rin	-	100	-	Ω
Differential Data Input Swing	Vin	150	-	1200	mV
Transmit Disable Voltage	VD	2.0	-	VCC+0.3	V
Transmit Enable Voltage	Ven	Vee	-	Vee+0.8	V

Receiver Specifications

Parameter	Symbol	Min	Typical	Max	Unit
Differential Data Output Swing	Vout	300	-	700	mV
Bit Error Rate	BER	-	-	10 ⁻¹²	-
Output Differential Impedance	Rout	-	100	-	Ω
Loss of Signal –Asserted	-	2.0	-	VCC+0.3	V
Loss of Signal –Negated	-	Vee	-	Vee+0.8	V

Sfp+ Transceiver Electrical Pad Layout



Pin Definition

Pin	Symbol	Name/Description
1	VEET [1]	Transmitter Ground
2	Tx_FAULT [2]	Transmitter Fault
3	Tx_DIS [3]	Transmitter Disable. Laser output disabled on high or open
4	SDA [2]	2-wire Serial Interface Data Line
5	SCL [2]	2-wire Serial Interface Clock Line
6	MOD_ABS [4]	Module Absent. Grounded within the module
7	RS0 [5]	Rate Select 0
8	RX_LOS [2]	Loss of Signal indication. Logic 0 indicates normal operation
9	RS1 [5]	Rate Select 1

Information and specifications are subject to change without notice. Please visit www.china-tscom.com for more information

10	VEER [1]	Receiver Ground
11	VEER [1]	Receiver Ground
12	RD-	Receiver Inverted DATA out. AC Coupled
13	RD+	Receiver DATA out. AC Coupled
14	VEER [1]	Receiver Ground
15	VCCR	Receiver Power Supply
16	VCCT	Transmitter Power Supply
17	VEET [1]	Transmitter Ground
18	TD+	Transmitter DATA in. AC Coupled
19	TD-	Transmitter Inverted DATA in. AC Coupled
20	VEET [1]	Transmitter Ground

Notes:

[1] Module circuit ground is isolated from module chassis ground within the module.

[2] Should be pulled up with 4.7k – 10k ohms on host board to a voltage between 3.15V and 3.45V.

[3] Tx_Disable is an input contact with a 4.7 kΩ to 10 kΩ pullup to VccT inside the module.

[4] Mod_ABS is connected to VeeT or VeeR in the SFP+ module. The host may pull this contact up to VCC_Host with a resistor in the range 4.7 kΩ to 10 kΩ. Mod_ABS is asserted “High” when the SFP+ module is physically absent from a host slot.

[5] RS0 and RS1 are module inputs and are pulled low to VeeT with > 30 kΩ resistors in the module.

Ordering Information

Part Number	Product Description
TSPA-85192-XXXC	SFP+ 10G Active Optical Cables 0°C ~ +70°C
XXX :001~082,1~82 Length in meters on OM2 MMF	
XXX :001~300,1~300 Length in meters on OM3 MMF	

Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by T&S before they become applicable to any particular order or contract. In accordance with the T&S policy of continuous improvement specifications may change without notice.

The publication of information in this data sheet does not imply freedom from patent or other protective rights of T&S or others. Further details are available from any T&S sales representative.