

TSSP-8525G-SR Optical Transceiver

850nm SFP+ Multi-mode Transceiver, With Diagnostic Monitoring
Duplex SFP+ 100m Transceiver, RoHS 6 Compliant

Features

- Supports 25.78Gb/s bit rate
- 850nm VCSEL laser and PIN photo-detector
- Maximum link length of 70m on OM3 MMF and 100m on OM4 MMF
- Digital diagnostics functions are available via the I2C interface
- Operating case temperature
- Commercial: 0°C to +70 °C
- +3.3V single power supply
- Power consumption less than 1W
- RoHS compliant
- Password protection for A0h and A2hRoHS6 compliant (lead free)



Applications

- 25GBASE-SR Ethernet
- 32G Fiber Channel
- Other optical links

Absolute Maximum Rating

These values represent the damage threshold of the module. Stress in excess of any of the individual Absolute Maximum Ratings can cause immediate catastrophic damage to the module even if all other parameters are within Recommended Operating Conditions.

Parameters	Symbol	Min.	Max.	Unit
Power Supply Voltage	V _{CC}	0	+3.6	V
Storage Temperature	T _c	-40	+85	°C
Operating Case Temperature	T _c	0	+70	°C

Relative Humidity	RH	5	95	%
RX Input Average Power	Pmax	-	0	dBm

Recommended Operating Environment

Recommended Operating Environment specifies parameters for which the electrical and optical characteristics hold unless otherwise noted.

Parameter	Symbol	Min.	Typical	Max	Unit
Power Supply Voltage	V _{CC}	3.135	3.300	3.465	V
Operating Case Temperature	T _C	0	25	70	°C

Optical Characteristics

The following optical characteristics are defined over the Recommended Operating Environment unless otherwise specified.

Parameter	Symbol	Min.	Typical	Max	Unit	Notes
Transmitter						
Center Wavelength	λ_t	820	850	880	nm	
RMS spectral width	P _m	-	-	0.6	nm	
Average Optical Power	P _{avg}	-5.0	-	2.4	dBm	2
Extinction Ratio	ER	2.0	-	-	dB	3
Transmitter Dispersion Penalty	TDP	-	-	3.9	dB	
Optical Return Loss Tolerance		-	-	12	dB	
Receiver						
Center Wavelength	λ_r	820		880	nm	
Receiver Sensitivity	P _{sens}	-	-	-5.2	dBm	3
Los function	Los	-30	-	-12	dBm	
Overload Input Optical	P _{in}	2.4	-	-	dBm	
Receiver Reflectance		-	-	-12	dB	

Note:

- Trade-offs are available between spectral width, center wavelength and minimum OMA, as shown in table 6.
- The optical power is launched into MMF
- Measured with a PRBS 2³¹-1 test pattern @25.78125Gbps; BER=5x10⁻⁵

Electrical Characteristics

The following electrical characteristics are defined over the Recommended Operating Environment unless otherwise specified.

Parameter	Symbol	Min.	Typical	Max	Unit	Notes
Data Rate	-	-	25.78125	-	Gbps	-
Power Consumption	-	-	1200	1500	mW	-

Transmitter						
Single Ended Output Voltage Tolerance	-	-0.3	-	4.0	V	-
C common mode voltage tolerance	-	15	-	-	mV	-
Tx Input Diff Voltage	VI	400	-	1600	mV	-
Tx Fault	VoL	-0.3	-	0.4	V	At 0.7mA
Receiver						
Single Ended Output Voltage Tolerance	-	-0.3	-	4.0	V	-
Rx Output Diff Voltage	Vo	300	-	850	mV	-

Pin Definition

Pin	Symbol	Name/Description
1	VEET [1]	Transmitter Ground
2	Tx_FAULT [2]	Transmitter Fault
3	Tx_DIS [3]	Transmitter Disable. Laser output disabled on high or open
4	SDA [2]	2-wire Serial Interface Data Line
5	SCL [2]	2-wire Serial Interface Clock Line
6	MOD_ABS [4]	Module Absent. Grounded within the module
7	RS0 [5]	Rate Select 0
8	RX_LOS [2]	Loss of Signal indication. Logic 0 indicates normal operation
9	RS1 [5]	Rate Select 1
10	VEER [1]	Receiver Ground
11	VEER [1]	Receiver Ground
12	RD-	Receiver Inverted DATA out. AC Coupled
13	RD+	Receiver DATA out. AC Coupled
14	VEER [1]	Receiver Ground
15	VCCR	Receiver Power Supply
16	VCCT	Transmitter Power Supply
17	VEET [1]	Transmitter Ground
18	TD+	Transmitter DATA in. AC Coupled
19	TD-	Transmitter Inverted DATA in. AC Coupled
20	VEET [1]	Transmitter Ground

Notes:

[1] Module circuit ground is isolated from module chassis ground within the module.

[2].should be pulled up with 4.7k – 10k ohms on host board to a voltage between 3.15V and 3.6V.

[3]Tx_Disable is an input contact with a 4.7 kΩ to 10 kΩ pullup to VccT inside the module.

[4]Mod_ABS is connected to VeeT or VeeR in the SFP+ module. The host may pull this contact up to Vcc_Host with a resistor in

the range 4.7 kΩ to 10 kΩ. Mod_ABS is asserted "High" when the SFP+ module is physically absent from a host slot.
 [5] RS0 and RS1 are module inputs and are pulled low to VeeT with > 30 kΩ resistors in the module.

Regulatory Compliance

T&S SFP+ transceiver is designed to be Class I Laser safety compliant and is certified per the following standards:

Feature	Agency	Standard	Certificate / Comments
Laser Safety	FDA	CDRH 21 CFR 1040 and Laser Notice No. 50	1120292-000
Product Safety	UL	UL and CUL EN60950-2:2007	E347511
Environmental protection	SGS	RoHS Directive 2002/95/EC	GZ1001008918/CHEM
EMC	WALTEK	EN 55022:2006+A1:2007 EN 55024:1998+A1+A2:2003	WT10093759-D-E-E

Ordering Information

Part Number	Product Description
TSSP-8525G-SR	25.78125Gbps SFP28 70m on OM3 MMF and 100m on OM4 MMF 0°C ~ +70°C

Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by T&S before they become applicable to any particular order or contract. In accordance with the T&S policy of continuous improvement specifications may change without notice.

The publication of information in this data sheet does not imply freedom from patent or other protective rights of T&S or others. Further details are available from any T&S sales representative.